

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Product name: Mixed organic solvent

Product code(SDS NO): SDS_sample_EU_E-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the product: Industrial use

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Asahi Graphic Corporation

Address: KOHGA Bldg. 3F, 4-23-8 Ebisu, Shibuya-KU, Tokyo, 150-0013 Japan

Telephone number: +81-3-5424-3016

FAX: +81-3-5424-3018

1.4 Emergency telephone number (24h): +81-3-****-****

2. Hazards identification

GHS classification and label elements of the product

2.1 Classification of the substance or mixture

Physical and chemical hazards

Flammable liquids: Category 2

HEALTH HAZARDS

Acute toxicity Inhalation: Category 4

Skin corrosion/irritation: Category 2

Reproductive toxicity: Category 2

Specific target organ toxicity – single exposure: Narcosis Category 3

Specific target organ toxicity – repeated exposure: Category 2

Aspiration hazard: Category 1

(Note) GHS classification without description: Not applicable/Out of classification/Not classifiable

2.2 Label elements



Signal word: Danger

HAZARD STATEMENT

H225 Highly flammable liquid and vapor

H332 Harmful if inhaled

H315 Causes skin irritation

H361 Suspected of damaging fertility or the unborn child

H336 May cause drowsiness or dizziness

H373 May cause damage to organs through prolonged or repeated exposure

H304 May be fatal if swallowed and enters airways

PRECAUTIONARY STATEMENT

Prevention

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

- P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P264 Wash contaminated parts thoroughly after handling.
 P280 Wear protective gloves.
 P280 Wear protective gloves and face protection.
 P280 Use personal protective equipment as required.

Response

- P370 + P378 In case of fire: Use appropriate media other than water for extinction.
 P321 Specific treatment is required.
 P314 Get medical advice/attention if you feel unwell.
 P308 + P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P332 + P313 If skin irritation occurs: Get medical advice/attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P331 Do NOT induce vomiting.
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Storage

- P403 Store in a well-ventilated place. P233 Keep container tightly closed. P235 Keep cool.
 P405 Store locked up.

Disposal

- P501 Dispose of contents/container in accordance with local/national regulation.

The product does not contain any ingredient designated as PBT and/or vPvB.

Physical and Chemical hazards

Highly flammable liquid. Vapor/air mixture may explode.

3. Composition/information on ingredients

Mixture/Substance selection:

3.2 Mixture

Ingredient name	CAS No.	Content(%)
HAZCODE_EU	ECNO	
Xylene (Mixture of isomers)	1330-20-7	40 - 45
Flam. Liq. 3, H226; Acute Tox. 4, H332; Acute Tox. 4, H312; Skin Irrit. 2, H315	215-535-7	
Ethylbenzene	100-41-4	40 - 45
Flam. Liq. 2, H225; Acute Tox. 4, H332; STOT RE 2, H373; Asp. Tox. 1, H304	202-849-4	
Polar solvent	CBI	20 - 25
Flam. Liq. 2, H225; Repr. 2, H361; Asp. Tox. 1, H304; STOT RE 2, H373; Skin Irrit. 2, H315; STOT SE 3, H336	203-625-9	

Note : The figures shown above are not the specifications of the product.

Components contributing to the hazard

- Not contain PBT/vPvB, REACH SVHC listed ingredient
- Not contain CMR, REACH SVHC listed ingredient
- Not contain Health, REACH SVHC listed ingredient
- Not contain Enviro, REACH SVHC listed ingredient

4. First-aid measures

4.1 Descriptions of first-aid measures

IF INHALED

Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN (or hair)

Take off immediately all contaminated clothing. Rinse skin with water/shower.
Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.

IF IN EYES

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

IF SWALLOWED

Do NOT induce vomiting.
Immediately call a POISON CENTER or doctor/physician.

4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment is required.

5. Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire, use water mist, foam, dry powder, CO₂.

Unsuitable extinguishing media

Do not use direct water jet.

5.2 Specific hazards arising from the substance or mixture

Will form toxic carbon oxides, hydrogen chloride upon combustion.

5.3 Advice for firefighters

Specific fire-fighting measures

Eliminate all ignition sources if safe to do so.
Cool container with water spray.

Special protective equipment and precautions for fire-fighters

Wear fire/flame resistant/retardant clothing.
Firefighters should wear self-contained breathing apparatus with full face piece operated positive pressure mode.

6. Accidental release measures

6.1 Personnel precautions, protective equipment and emergency procedures

Evacuate area.
Keep unauthorized personnel away.
Wear an air-supplied respirator for a poor/non ventilated spill.
Wear proper protective equipment.
Eliminate all sources of ignition and ventilate the area.

6.2 Environmental precautions

Prevent spills from entering sewers, watercourses or low areas.

6.3 Methods and materials for containment and cleaning up

Absorb spill with inert material (dry sand, earth, et al), then place in a chemical waste container.
Fill the disposal into labelled, closable containers.

Preventive measures for secondary accident

Collect spillage.
Prepare extinguishers before catching fire.

7. Handling and storage

7.1 Precautions for safe handling

Preventive measures

(Exposure Control for handling personnel)

Do not breathe gas/mist/vapors/spray.

(Protective measures against fire and explosion)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Safety treatments

Avoid contact with skin.

Avoid contact with eyes.

Safety Measures/Incompatibility

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wear protective gloves and face protection.

Use personal protective equipment as required.

7.2 Conditions for safe storage, including any incompatibilities

Recommendation for storage

Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Protect from sunlight.

8. Exposure controls/personal protection

8.1 Control parameters

Adopted value

(Ethylbenzene)

ACGIH(2010) TWA: 20ppm

(URT irr; kidney dam; nephropathy; cochlear impair)

(Polar solvent)

ACGIH(2006) TWA: 20ppm (Visual impair; female repro; pregnancy loss)

(Xylene (Mixture of isomers))

ACGIH(1992) TWA: 100ppm

STEL: 150ppm (URT & eye irr; CNS impair)

8.2 Exposure controls

Appropriate engineering controls

Exhaust/ventilator should be available.

Eye wash station should be available.

Washing facilities should be available.

Individual protection measures

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Wear protective gloves. Recommended material(s): impermeable or chemical resistant rubber

Eye protection

Wear safety glasses with side-shields or chemical safety goggle.

Skin and body protection

Wear protective clothing.

Safety and Health measures

Wash ... thoroughly after handling.

Do not eat, drink or smoke when using this product.
Take off contaminated clothing and wash it before reuse.
Wash hands thoroughly after handling.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Physical properties

Appearance: Liquid

Color: Clear

Odor: Solvent odor

Phase change temperature

Initial Boiling Point/Boiling point: 115°C

Flash point: (Tag closed cup)5°C

Specific gravity/Density: 0.91(20°C)

Kinematic viscosity: 15.1mm²/s(20°C)

Solubility

Solubility in water: Insoluble

10. Stability and Reactivity

10.2 Chemical stability

Stable under normal storage/handling conditions.

10.5 Incompatible materials

Oxidizing agents

10.6 Hazardous decomposition products

Carbon oxides

11. Toxicological Information

11.1 Information on toxicological effects

No Acute toxicity data available

No Irritant properties data available

No Allergenic and sensitizing effects data available

No Mutagenic effects data available

Carcinogenicity

(Ethylbenzene)

IARC-Gr.2B : Possibly carcinogenic to humans

(Polar solvent)

IARC-Gr.3 : Not Classifiable as a Human Carcinogen

(Xylene (Mixture of isomers))

IARC-Gr.3 : Not Classifiable as a Human Carcinogen

(Xylene (Mixture of isomers))

ACGIH-A4(1992) : Not Classifiable as a Human Carcinogen

(Ethylbenzene)

ACGIH-A3(2010) : Confirmed Animal Carcinogen with Unknown Relevance to Humans

(Polar solvent)

ACGIH-A4(2006) : Not Classifiable as a Human Carcinogen

No Teratogenic effects data available

No reproductive toxicity data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure

STOT

STOT-repeated exposure

[cat.2]

[EU CLP name of STOT]

(Ethylbenzene)

hearing organs

No Aspiration hazard data available

12. Ecological Information

12.1 Ecotoxicity

No Aquatic toxicity data available

Water solubility

(Ethylbenzene)

0.015 g/100 ml (20°C) (ICSC, 2007)

(Polar solvent)

none (ICSC, 2002)

12.2 Persistence and degradability

(Xylene (Mixture of isomers))

Not degrade rapidly (BOD_Degradation : 39% (NITE risk primary assessment, 2005))

(Ethylbenzene)

Not degrade rapidly (BOD_Degradation : 0% (MITI official bulletin, 1990))

(Polar solvent)

BOD_Degradation : 123% (Registered chemicals data check & review, Japan)

12.3 Bioaccumulative potential

(Xylene (Mixture of isomers))

log Pow=3.16 (PHYSPROP Database, 2005)

(Ethylbenzene)

log Kow=3.15 (PHYSPROP Database, 2005)

(Polar solvent)

log Kow=2.73 (PHYSPROP Database, 2008)

No Mobility in soil data available

Ozone depleting chemical data not available

13. Disposal considerations

13.1 Waste treatment methods

Avoid release to the environment (– if this is not the intended use).

Dispose of contents/container in accordance with local/national regulation.

Dispose to an authorized waste collection point.

14. Transport Information

UN No, UN CLASS

14.1 UN number: 1993

14.2 UN proper shipping name:

FLAMMABLE LIQUID, N.O.S.

14.3 Transport hazard class(es): 3

14.4 Packing group: II

ERG GUIDE NO.: 128

14.7 Transport in bulk according to Annex II of MARPOL73/78 and IBC Code

Noxious Liquid ; Cat. Y

Ethylbenzene; Xylene (Mixture of isomers); Polar solvent

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or

mixture

Data N.A.

Other regulatory information

We are not able to check up other regulatory information in regard to the substances in your country or region, therefore we request this matter would be filled by your responsibility.

16. Other information

GHS classification and labelling

Flam. Liq. 2: H225 Highly flammable liquid and vapor

Acute Tox. 4: H332 Harmful if inhaled

Skin Irrit. 2: H315 Causes skin irritation

Repr. 2: H361 Suspected of damaging fertility or the unborn child

STOT SE 3: H336 May cause drowsiness or dizziness

STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure

Asp. Tox. 1: H304 May be fatal if swallowed and enters airways

Reference Book

Globally Harmonized System of classification and labelling of chemicals, (5th ed., 2013), UN

Recommendations on the TRANSPORT OF DANGEROUS GOODS 19th edit., 2015 UN

Classification, labelling and packaging of substances and mixtures (table3-1 ECNO6182012)

2016 EMERGENCY RESPONSE GUIDEBOOK (US DOT)

2018 TLVs and BEIs. (ACGIH)

<http://monographs.iarc.fr/ENG/Classification/index.php>

Supplier's data/information

Chemicals safety data management system "GHS Assistant" Asahi Graphic Corporation

GESTIS-Stoffdatenbank

Pub Chem (OPEN CHEMISTRY DATABASE)

General Disclaimer

This information contained in this data sheet represents the best information currently available to us. However, no warranty is made with respect to its completeness and we assume no liability resulting from its use. It are advised to make their own tests to determinate the safety and suitability of each such product or combination for their own purposes.

The GHS classification data given here is based on current EU official data (EU CLP published in 01.03.2018).